


# EARTHMAX SR 49 M

**29.5 R 25**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	DOZER / YÜK TAŞIMA DAMPERİ (LHD) / YÜKLEYİCİ / DÜŞÜK PROFİLLİ DAMPERLİ KAMYON
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
	200 B ; 216 A2



## UNDEFINED US STANDARD

<b>USA CODE</b>	94516766	<b>RIM REC</b>	25.00/3.5
<b>OD (IN)</b>	75.0	<b>TRA CODE</b>	E4/L4
<b>SLR (IN)</b>	33.2	<b>STAR RATING</b>	★★
<b>RC (IN)</b>	220.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69	73	76	80	83	87	91	94
30	25400	26000	27600	28300	30000	30900	-	-	-	-	-
5	-	-	-	-	-	41900	43000	44100	45400	46700	49400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.