


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>580/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	577	<b>RIM REC</b>	W 18 L
<b>OD (MM)</b>	1827	<b>ECE</b>	E4-106R-000809
<b>SLR (MM)</b>	821	<b>SRI</b>	875
<b>RC (MM)</b>	5505	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	4.6
50	3180	3875	4490	4990	5460	5890	6310	6710	7090	7280
40	3180	3875	4930	5480	6000	6470	6930	7370	7790	8000
30	3405	4150	5280	5860	6420	6920	7420	7890	8340	8560
25	3535	4305	5470	6080	6660	7180	7690	8180	8650	8880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.