

# AW 09

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>380/55 - 17</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | BIAS  |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / CEIFEIRA / IMPLEMENTOS<br>AGRÍCOLAS / CEIFEIRA |
| <b>VERSÃO</b>             | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 128 A8  |
| <b>LI/SS FREE ROLLING</b> | 141 A8  |



## DIMENSÕES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94038060 | <b>RC (IN)</b> | 98.1           |
| <b>SW (IN)</b>    | 15.4     | <b>RIM REC</b> | 13.00          |
| <b>OD (IN)</b>    | 33.5     | <b>ECE</b>     | E4-106R-000380 |
| <b>SLR (IN)</b>   | 14.8     |                |                |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>46</b> |
|------------------|-----------|
| 5 FR             | 7950      |
| 15 FR            | 6760      |
| 20 FR            | 6360      |
| 25 FR            | 5680      |
| 5 DW             | 5560      |
| 15 DW            | 4720      |
| 20 DW            | 4440      |
| 25 DW            | 3970      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.