


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 250/85 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS / VINEYARD HARVESTER / HARVESTER |
| VERSION | SPECIAL |
| TL/TT | TL |
| LI/SS | 109 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94046751 | RC (IN) | 122.2 |
| SW (IN) | 9.9 | RIM REC | W 8 |
| OD (IN) | 40.8 | RIM ALT | W 7 ; W 9 |
| SLR (IN) | 18.7 | ECE | E4-106R-000638 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 1260 | 1450 | 1660 | 1860 | 2070 | 2270 |
| 25 | 1260 | 1450 | 1660 | 1860 | 2070 | 2270 |
| 20 | 1340 | 1570 | 1790 | 2010 | 2230 | 2440 |
| 5 LT | 1690 | 1960 | 2240 | 2510 | 2790 | 3050 |
| 5 HT | 1340 | 1570 | 1790 | 2010 | 2230 | 2440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.