


# EARTHMAX SR 22

<b>TIRE SIZE</b>	<b>15.5 R 25</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	AUTOGREDER / ÎNCĂRCĂTOR / BULDOZER / ÎNCĂRCĂTOR / BULDOZER / AUTOGREDER
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 A8 ; 169 A2



## DIMENSIUNI IS STANDARD

<b>OD (MM)</b>	1275	<b>TRA CODE</b>	G2/L2
<b>SLR (MM)</b>	557	<b>STAR RATING</b>	★
<b>RC (MM)</b>	3841		
<b>RIM REC</b>	12.00/1.3		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00
40	1550	1750	2000	2180	2360	2575	2800	3000	-	-	-	-	-
10	-	-	-	-	-	-	-	-	5000	5150	5450	5600	5800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.