


# AGRIMAX RT 855

<b>TYRE SIZE</b>	<b>320/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	124 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94047352	<b>RC (IN)</b>	147.4
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	49.4	<b>RIM ALT</b>	W 9; W 10
<b>SLR (IN)</b>	22.4	<b>ECE</b>	E4-106R-000615

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3520
25	1940	2260	2580	2900	3220	3520
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.