


# AGRIMAX FORCE

<b>TYRE SIZE</b>	<b>IF 650/65 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	161 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94060054	<b>RC (IN)</b>	199.9
<b>SW (IN)</b>	25.6	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	67.3	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	30.1	<b>ECE</b>	E4-106R-001826

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23
45	5190	6120	6940	7790	8530	9270
<b>FROM 40 TO 25</b>	5710	6720	7640	8560	9380	10200
20	5930	6990	7940	8910	9750	10600
12	6160	725	8240	9250	10130	11010
5	7240	8530	9700	10870	11900	12940
<b>UPTO 20 CYC</b>	7420	8740	9920	11120	12190	13250
<b>UPTO 10 CYC</b>	8840	10420	11840	13270	14540	15800
<b>UPTO 5 CYC</b>	9700	11430	12980	14550	15940	17330
5HT	5930	6990	7940	8910	9750	10600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.