

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 700/50 - 26.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 162 A8/158 B |
| LI/SS FREE ROLLING | 174 A8/170 B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94006526 | RC (IN) | 161.4 |
| SW (IN) | 27.6 | RIM REC | 24.00 |
| OD (IN) | 54.1 | ECE | E4-106R-002279 |
| SLR (IN) | 24.4 | PR | 16 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 29 | 32 | 35 |
|--------------|-------|-------|-------|
| 5 FR | 18580 | 19640 | 20680 |
| 10 FR | 16720 | 17680 | 18610 |
| 20 FR | 14860 | 15720 | 16540 |
| 25 FR | 13270 | 14030 | 14770 |
| 30 FR | 11950 | 12630 | 13230 |
| 5 DW | 13180 | 13930 | 14660 |
| 10 DW | 11860 | 12540 | 13190 |
| 20 DW | 10540 | 11140 | 11730 |
| 25 DW | 9410 | 9950 | 10470 |
| 30 DW | 8480 | 8960 | 9370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.