

AW 708

| | |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| TIRE SIZE | 500/65 - 17 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 160 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94034307 | RC (IN) | 123.4 |
| SW (IN) | 20.7 | RIM REC | 16.0 |
| OD (IN) | 42.5 | ECE | E11-106R-004549 |
| SLR (IN) | 18.2 | PR | 18 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 51 |
|-----------|-------|
| 5 FR | 13890 |
| 15 FR | 11810 |
| 20 FR | 11110 |
| 25 FR | 9920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.