


# RT 853

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>480/80 R 38</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR / VENDIMIADORA / COSECHADORA   |
| <b>VERSIÓN</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 149 A8/B   |



## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 475  | <b>RIM REC</b> | W 16 L         |
| <b>OD (MM)</b>  | 1747 | <b>RIM ALT</b> | W 15 L; W 14 L |
| <b>SLR (MM)</b> | 793  | <b>ECE</b>     | E4-106R-001822 |
| <b>RC (MM)</b>  | 5300 | <b>SRI</b>     | 825            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 40         | 1790 | 2080 | 2375 | 2665 | 2960 | 3250 |
| 30         | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |
| 10 LT      | 2400 | 2790 | 3180 | 3575 | 3965 | 4355 |
| 10 HT      | 1915 | 2230 | 2545 | 2855 | 3170 | 3480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.