


RIDEMAX FL 693 M



TIRE SIZE	500/60 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKBIL / SLÄPVAGN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	155 D ; 152 E

DIMENSIONER US STANDARD

USA CODE	94040605	RC (IN)	140.8
SW (IN)	19.8	RIM REC	AG 16.00
OD (IN)	46.1	RIM ALT	15.00; 17.00
SLR (IN)	20.9	ECE	E4-106R-001402

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	2910	3300	3910	4620	5290	5870	6580	7210	7830
40	3160	3590	4280	5050	5780	6420	7180	7860	8540
30	3840	4340	5170	6110	6990	7760	8690	9510	10340
25	4310	4880	5810	6860	7850	8720	9770	10690	11620
15	5000	5680	6760	7970	9120	10130	11340	12420	13500
5	5700	6460	7690	9080	10380	11540	12920	14150	15380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.