

# PL 801

<b>TIRE SIZE</b>	<b>5.00 - 8</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ROTTERANDE HARV / SKÖRDEMASKIN / GAFFELTRUCK / SKÖRDEMASKIN / ARBETSFORDON / GAFFELTRUCK
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94032259	<b>RIM ALT</b>	3.25 I
<b>SW (IN)</b>	5.3	<b>PR</b>	10
<b>OD (IN)</b>	18.4		
<b>RIM REC</b>	3.00 D		

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>145</b>
<b>15 LOAD WHEEL</b>	3120
<b>15 STEER WHEEL</b>	2405
<b>5 OTHER VEHICLES</b>	3120
<b>15 OTHER VEHICLES</b>	2405
<b>STATIC SIDE LOADER</b>	3625

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.