


# AS 504

<b>TIRE SIZE</b>	<b>5.00 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	75 A8
<b>LI/SS FREE ROLLING</b>	88 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	140	<b>RIM REC</b>	3.50 D
<b>OD (MM)</b>	657	<b>RIM ALT</b>	3.00 D; 4.00 E; 4 J
<b>SLR (MM)</b>	308	<b>ECE</b>	E4-106R-001950
<b>RC (MM)</b>	1957	<b>PR</b>	6

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.50
10 FR	785
25 FR	665
30 FR	625
40 FR	560
10 DW	540
25 DW	460
30 DW	430
40 DW	385

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.