


MULTIMAX MP 513

| | |
|---------------------|--|
| TYRE SIZE | 325/70 R 18 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | UNIVERSAL VEHICLE / UNIVERSAL VEHICLE |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 132 G |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94074488 | RC (IN) | 109.1 |
| SW (IN) | 12.7 | RIM REC | W 10 |
| OD (IN) | 36.1 | ECE | E11-54R-0020959 |
| SLR (IN) | 16.1 | | |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 23 | 29 | 36 | 44 | 51 |
|-----------|------|------|------|------|------|
| 55 | 2410 | 2830 | 3370 | 3900 | 4410 |
| 40 | 2600 | 3060 | 3640 | 4220 | 4760 |
| 25 | 2770 | 3260 | 3880 | 4500 | 5070 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.