


# AGRIMAX RT 600

**800/65 R 32**

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	181 A8 ; 178 B



## UNDEFINED IS STANDARD

SW (MM)	775	RIM REC	DW 27 B
OD (MM)	1820	RIM ALT	DH 27 B ; DW 25 B
SLR (MM)	823	ECE	E4-106R-001429
RC (MM)	5558	SRI	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	3175	3660	4485	4900	5385	5865	6350	6900	7500	-	-
40	3450	3975	4875	5325	5850	6375	6900	7500	8250	-	-
30	3695	4255	5220	5700	6260	6825	7385	8025	8830	-	-
10 LT	4625	5330	6535	7140	7840	8545	9250	10050	11055	-	-
10 HT	3695	4255	5220	5700	6260	6825	7385	8025	8830	-	-
10 CYC	-	5655	7230	7960	9250	10140	11055	12025	12440	13000	14000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.