


AGRIMAX V- FLECTO

TIRE SIZE	VF 340/85 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	139 D



РАЗМЕРЫ US STANDARD

USA CODE	94076369	RC (IN)	150.9
SW (IN)	14.0	RIM REC	W 12
OD (IN)	50.8	RIM ALT	W 11
SLR (IN)	22.5	ECE	E11-106R-0010342

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	2680	3110	3550	3990	4430	4870
FROM 40 TO 25	2940	3430	3900	4390	4870	5360
20	3000	3480	3980	4460	4960	5460
12	3050	3560	4060	4560	5060	5570
5	3530	4710	5890	7050	8350	9890
*UPTO 5 CYC WITH FRONT LOADER	4120	4790	5470	6140	6810	7500
10HT	3000	3480	3980	4460	4960	5460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.