


# AGRIMAX RT 855

<b>TYRE SIZE</b>	<b>280/85 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	118 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	292	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	1187	<b>RIM ALT</b>	W 9
<b>SLR (MM)</b>	545	<b>ECE</b>	E4-106R-000614
<b>RC (MM)</b>	3558	<b>SRI</b>	575

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	730	845	965	1085	1205	1320
40	730	845	965	1085	1205	1320
30	780	910	1035	1165	1290	1415
10 LT	975	1135	1295	1455	1615	1770
10 HT	780	910	1035	1165	1290	1415

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.