



US standard



MAGLIFT PLUS



PRODUCT DATA SHEET



Solid



MAGLIFT PLUS

MAGLIFT PLUS has been specifically developed to provide excellent productivity in demanding forklift operations in industrial and intralogistics environments. Designed for intensive indoor and outdoor use on smooth surfaces, the tire features a full depth tread design with lateral and circumferential grooves maintaining consistent steering control as well as both lateral and forward traction in a variety of critical conditions throughout the entire tire life. These include e.g. high average speeds, rapid acceleration/deceleration, tight maneuvering and high stacking operations. Moreover, the semi closed tread center minimizes vibration providing enhanced operator comfort during multi shift operations. Thanks to a particularly cut-and-chip-resistant compound and a reinforced structure, MAGLIFT PLUS is an extraordinarily durable tire that stands out for its resistance against wear and damages even under constant heavy loads resulting in the lowest possible cost per hour. Available with a marking and *non-marking* compound and as standard or "lip" version.

Performance



Traction



Comfort



Cut and Chip Resistance



Durability



High Load Capacity

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 8"	94521067	16 X 6 - 8 (150/75 - 8)	-	-	-	STD	16.6	6.0	-	-	49	35	4.33 R - 8	-
	94519927	16 X 6 - 8 (150/75 - 8)	-	-	-	STD-NM	16.6	6.0	-	-	49	35	4.33 R - 8	-
	94521081	16 X 6 - 8 (150/75 - 8)	-	-	-	LIP	16.6	6.0	-	-	49	35	4.33 R - 8	-
	94519941	16 X 6 - 8 (150/75 - 8)	-	-	-	LIP-NM	16.6	6.0	-	-	49	36	4.33 R - 8	-
	94521302	18 X 7 - 8 (180/70 - 8)	-	-	-	STD	18.0	6.0	-	-	56	44	4.33 R - 8	-
	94519873	18 X 7 - 8 (180/70 - 8)	-	-	-	STD-NM	18.0	6.0	-	-	56	44	4.33 R - 8	-
	94521326	18 X 7 - 8 (180/70 - 8)	-	-	-	LIP	18.0	6.0	-	-	56	45	4.33 R - 8	-
	94519897	18 X 7 - 8 (180/70 - 8)	-	-	-	LIP-NM	18.0	6.0	-	-	56	45	4.33 R - 8	-
Ø 9"	94520961	140/55 - 9	-	-	-	STD	14.8	5.1	-	-	30	21	4.00 E - 9	-
	94520701	140/55 - 9	-	-	-	STD-NM	14.8	5.1	-	-	30	21	4.00 E - 9	-
	94520985	140/55 - 9	-	-	-	LIP	14.8	5.1	-	-	30	21	4.00 E - 9	-
	94520725	140/55 - 9	-	-	-	LIP-NM	14.8	5.1	-	-	30	22	4.00 E - 9	-
Ø 10"	94521340	200/50 - 10	-	-	-	STD	18.0	7.5	-	-	45	51	6.50 F - 10	-
	94518814	200/50 - 10	-	-	-	STD-NM	18.0	7.5	-	-	45	51	6.50 F - 10	-
	94521364	200/50 - 10	-	-	-	LIP	18.0	7.5	-	-	45	52	6.50 F - 10	-
	94518838	200/50 - 10	-	-	-	LIP-NM	18.0	7.5	-	-	45	51	6.50 F - 10	-
Ø 12"	94520404	23 X 10 - 12 (250/60 - 12)	-	-	-	STD	23.0	9.3	-	-	61	106	8.00 G - 12	-
	94520213	23 X 10 - 12 (250/60 - 12)	-	-	-	STD-NM	23.0	9.3	-	-	61	105	8.00 G - 12	-

STD: Standard - LIP: LIP Version - LIP-NM: LIP Non Marking - STD-NM: Standard Non Marking

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Solid

Performance



Traction



Comfort



Cut and Chip Resistance



Durability



High Load Capacity



	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 12"	94520428	23 X 10 - 12 (250/60 - 12)	-	-	-	LIP	23.0	9.3	-	-	61	106	8.00 G - 12	-
	94520237	23 X 10 - 12 (250/60 - 12)	-	-	-	LIP-NM	23.0	9.3	-	-	61	106	8.00 G - 12	-

LIP: LIP Version - LIP-NM: LIP Non Marking



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment. All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

EN-US / 06-2026

