DATA SHEET

Latest update
2-06-2026

SKID MAX SR-SKIDDER

TYRE SIZE	**260/70 R 16.5**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	TELEHANDLER / LOADER
VERSION	INDUSTRIAL
TL/TT	TL
LI/SS	129 A8/B

DIMENSIONS IS STANDARD

OD (MM)	776	**RIM ALT**	7.50 ; 9.00
SLR (MM)	352	**ECE**	E11-106R-006809
RC (MM)	2367		
RIM REC	8.25		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	5.00
40	1850
50	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..