

# TF 8181

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | 11.00 - 16                            |
| <b>UM</b>           | IS STANDARD                           |
| <b>CONSTRUCTION</b> | ❖ BIAS                                |
| <b>MACHINERY</b>    | TRACTEUR 2WD / TRACTEUR /<br>REMORQUE |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TT                                    |
| <b>LI/SS</b>        | 118 A6                                |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 326  | <b>RIM REC</b> | W 10 L         |
| <b>OD (MM)</b>  | 970  | <b>RIM ALT</b> | W 8; W 8 L     |
| <b>SLR (MM)</b> | 447  | <b>ECE</b>     | E4-106R-002673 |
| <b>RC (MM)</b>  | 2920 | <b>PR</b>      | 8              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.50</b> |
| 30                | 1320        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.