



IS standard



# MAGLIFT PLUS



PRODUCT DATA SHEET



Solid



# MAGLIFT PLUS

MAGLIFT PLUS has been specifically developed to provide excellent productivity in demanding forklift operations in industrial and intralogistics environments. Designed for intensive indoor and outdoor use on smooth surfaces, the tire features a full depth tread design with lateral and circumferential grooves maintaining consistent steering control as well as both lateral and forward traction in a variety of critical conditions throughout the entire tire life. These include e.g. high average speeds, rapid acceleration/deceleration, tight maneuvering and high stacking operations. Moreover, the semi closed tread center minimizes vibration providing enhanced operator comfort during multi shift operations. Thanks to a particularly cut-and-chip-resistant compound and a reinforced structure, MAGLIFT PLUS is an extraordinarily durable tire that stands out for its resistance against wear and damages even under constant heavy loads resulting in the lowest possible cost per hour. Available with a marking and *non-marking* compound and as standard or "lip" version.

**Performance**



Traction



Comfort



Cut and Chip Resistance



Durability



High Load Capacity

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 8"	16 X 6 - 8 (150/75 - 8)	-	-	-	STD	153	421	-	-	4.33 R - 8	-
	16 X 6 - 8 (150/75 - 8)	-	-	-	STD-NM	153	421	-	-	4.33 R - 8	-
	16 X 6 - 8 (150/75 - 8)	-	-	-	LIP	153	421	-	-	4.33 R - 8	-
	16 X 6 - 8 (150/75 - 8)	-	-	-	LIP-NM	153	421	-	-	4.33 R - 8	-
	18 X 7 - 8 (180/70 - 8)	-	-	-	STD	153	457	-	-	4.33 R - 8	-
	18 X 7 - 8 (180/70 - 8)	-	-	-	STD-NM	153	457	-	-	4.33 R - 8	-
	18 X 7 - 8 (180/70 - 8)	-	-	-	LIP	153	457	-	-	4.33 R - 8	-
	18 X 7 - 8 (180/70 - 8)	-	-	-	LIP-NM	153	457	-	-	4.33 R - 8	-
Ø 9"	140/55 - 9	-	-	-	STD	130	377	-	-	4.00 E - 9	-
	140/55 - 9	-	-	-	STD-NM	130	377	-	-	4.00 E - 9	-
	140/55 - 9	-	-	-	LIP	130	377	-	-	4.00 E - 9	-
	140/55 - 9	-	-	-	LIP-NM	130	377	-	-	4.00 E - 9	-
Ø 10"	200/50 - 10	-	-	-	STD	190	458	-	-	6.50 F - 10	-
	200/50 - 10	-	-	-	STD-NM	190	458	-	-	6.50 F - 10	-
	200/50 - 10	-	-	-	LIP	190	458	-	-	6.50 F - 10	-
	200/50 - 10	-	-	-	LIP-NM	190	458	-	-	6.50 F - 10	-
Ø 12"	23 X 10 - 12 (250/60 - 12)	-	-	-	STD	236	584	-	-	8.00 G - 12	-
	23 X 10 - 12 (250/60 - 12)	-	-	-	STD-NM	236	584	-	-	8.00 G - 12	-

STD: Standard - LIP: LIP Version - LIP-NM: LIP Non Marking - STD-NM: Standard Non Marking

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Solid



Performance



Traction



Comfort



Cut and Chip Resistance



Durability



High Load Capacity

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 12"	23 X 10 - 12 (250/60 - 12)	-	-	-	LIP	236	584	-	-	8.00 G - 12	-
	23 X 10 - 12 (250/60 - 12)	-	-	-	LIP-NM	236	584	-	-	8.00 G - 12	-

LIP: LIP Version - LIP-NM: LIP Non Marking



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment. All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.

