


AGRIMAX V- FLECTO



TIRE SIZE	VF 650/75 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	175 D

DIMENSIONES US STANDARD

CÓDIGO USA	94512164	RC (IN)	228.2
SW (IN)	26.6	RIM REC	DW 23 B
OD (IN)	76.4	RIM ALT	DW 21 B
SLR (IN)	32.8	ECE	E11-106R-0010663

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	7610	8850	10100	11340	12590	13830
FROM 40 TO 25	8370	9730	11100	12470	13830	15210
20	8520	9920	11320	12710	14110	15510
12	8700	10120	11540	12960	14380	15820
5	9190	10700	12210	13710	15220	16730
*UPTO 5 CYC WITH FRONT LOADER	11710	13620	15540	17460	19380	21300
5 HT	8520	9920	11320	12710	14110	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.