

AGRIMAX RT 955

TIRE SIZE	300/95 R 46
UM	US STANDARD
MACHINERY	SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	148 D ; 151 A8



DIMENSIONS US STANDARD

USA CODE	94076154	RIM ALT	W 10 ; W 11 ; DW 10 ; DW 11
SW (IN)	11.6	ECE	E11-106R-0010269
OD (IN)	68.4	TRA CODE	R1
SLR (IN)	32.0	TREAD DEPTH (32nd)	44.73
RC (IN)	209.4	TMPH (TM/H)	0
RIM REC	W 9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52	58
40	8110	8980	9850	10280	10860	11150	11440	12020	12600	13030
30	8770	9720	10640	11120	11740	12060	12370	12990	13630	14090
25	8940	9910	10860	11350	11990	12310	12630	13250	13900	14390
20	9120	10100	11070	11570	12220	12550	12870	13520	14170	14660
5	9650	10690	11710	12230	12920	13270	13610	14290	14980	15500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.