


FL 695

| | |
|---------------------|--|
| TIRE SIZE | 650/55 R 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | RIMORCHIO / ATTREZZI AGRICOLI / RIMORCHIO |
| VERSIONE | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 178 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 630 | RIM REC | AG20.00 |
| OD (MM) | 1390 | RIM ALT | AG22.00 |
| SLR (MM) | 630 | ECE | E11-106R-007052 |
| RC (MM) | 4242 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 | 5.0 | 5.5 | 6.0 |
|------------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 65 | -- | -- | -- | 3375 | 3900 | 4425 | 4875 | 5325 | 5850 | 6225 | 6600 | 7050 | 7500 |
| 50 | -- | -- | -- | 4085 | 4720 | 5355 | 5900 | 6445 | 7080 | 7535 | 7990 | 8535 | 9075 |
| 40 | -- | 3370 | 4185 | 4590 | 5305 | 6020 | 6630 | 7245 | 7960 | 8470 | 8980 | 9590 | 10200 |
| 30 | 2835 | 3740 | 4645 | 5100 | 5890 | 6685 | 7365 | 8045 | 8835 | 9400 | 9970 | 10650 | 11325 |
| 25 | 2965 | 3915 | 4860 | 5335 | 6165 | 6995 | 7705 | 8415 | 9245 | 9840 | 10430 | 11140 | 11850 |
| 20 | 3095 | 4085 | 5075 | 5570 | 6435 | 7305 | 8045 | 8790 | 9655 | 10275 | 10890 | 11635 | 12375 |
| 10 | 3375 | 4455 | 5535 | 6075 | 7020 | 7965 | 8775 | 9585 | 10530 | 11205 | 11880 | 12690 | 13500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.