


AGRIMAX FORCE



TIRE SIZE	IF 710/55 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	165 D

РАЗМЕРЫ US STANDARD

USA CODE	94059690	RC (IN)	174.9
SW (IN)	28.2	RIM REC	DW 25 B
OD (IN)	58.8	ECE	E11-106R-005498
SLR (IN)	26.1	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4740	5460	6290	7020	7840	8560	9590	10330
FROM 40 TO 25	5210	6010	6920	7720	8620	9410	10550	11400
20	5410	6240	7200	8020	8960	9790	10970	11810
12	5620	6480	7470	8330	9300	10160	11390	12260
5	6610	7630	8780	9800	10950	11950	13390	14420
UPTO 20 CYC	6770	7800	8990	10030	11200	12230	13710	14760
UPTO 10 CYC	8080	9300	10720	11960	13360	14580	16350	17590
UPTO 5 CYC	8860	10210	11760	13120	14650	15990	17920	19300
5 HT	5410	6240	7200	8020	8960	9790	10970	11810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.