


# AGRIMAX SPARGO

VF 380/90 R 46 CFO

|              |  |
|--------------|--|
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRAKTÖR  |
| VERSION      | STANDARD   |
| TIRE TYPE    | TL   |
|              | 175 D  |



## UNDEFINED US STANDARD

|          |          |         |                    |
|----------|----------|---------|--------------------|
| USA CODE | 94518494 | RC (IN) | 220.9              |
| SW (IN)  | 15.4     | RIM REC | DW 13 A            |
| OD (IN)  | 72.9     | RIM ALT | W 13 A ; DW 12     |
| SLR (IN) | 33.4     | ECE     | E11-106R-007527-01 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 17   | 20    | 23    | 26    | 29    | 32    | 35    | 38    | 41    | 44    | 46    | 49    | 52    | 55    | 58    | 61    | 64    | 67    |
|---------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 6250 | 7040  | 7690  | 8080  | 8470  | 8730  | 9000  | 9520  | 9910  | 10300 | 10700 | 11080 | 11350 | 11730 | 12000 | 12520 | 13040 | 13690 |
| FROM 40 TO 25 | 6880 | 7740  | 8460  | 8890  | 9320  | 9610  | 9890  | 10470 | 10900 | 11330 | 11750 | 12180 | 12470 | 12900 | 13190 | 13760 | 14330 | 15220 |
| 20            | 7020 | 7900  | 8620  | 9070  | 9500  | 9790  | 10080 | 10660 | 11100 | 11550 | 11990 | 12430 | 12710 | 13150 | 13440 | 14030 | 14620 | 15520 |
| 12            | 7150 | 8050  | 8790  | 9240  | 9680  | 9980  | 10280 | 10870 | 11330 | 11780 | 12220 | 12670 | 12970 | 13410 | 13710 | 14300 | 14910 | 15830 |
| 5*            | 7570 | 8510  | 9300  | 9770  | 10240 | 10560 | 10870 | 11500 | 11980 | 12450 | 12920 | 13400 | 13720 | 14190 | 14500 | 15130 | 15770 | 16740 |
| UPTO 10 CYC.  | 9330 | 10500 | 11470 | 12050 | 12640 | 13020 | 13410 | 14180 | 14760 | 15350 | 15930 | 16520 | 16900 | 17490 | 17870 | 18660 | 19430 | 20620 |
| UPTO 20 CYC.  | 7820 | 8800  | 9610  | 10100 | 10590 | 10920 | 11240 | 11890 | 12370 | 12870 | 13350 | 13840 | 14170 | 14650 | 14980 | 15630 | 16290 | 17280 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.