

# AT 621

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>400/70 - 20</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | BIAS   |
| <b>MACHINERY</b>    | CARGADORA COMPACTA /<br>CARGADORA RETROEXCAVADORA /<br>CARGADORA RETROEXCAVADORA /<br>PALA CARGADORA |
| <b>VERSIÓN</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 B ; 168 A2   |



## DIMENSIONES IS STANDARD

|                 |      |                 |                      |
|-----------------|------|-----------------|----------------------|
| <b>SW (MM)</b>  | 405  | <b>RIM REC</b>  | 13                   |
| <b>OD (MM)</b>  | 1090 | <b>RIM ALT</b>  | 12 SDC ; 13 SDC ; 14 |
| <b>SLR (MM)</b> | 494  | <b>PR</b>       | 16                   |
| <b>RC (MM)</b>  | 3271 | <b>TRA CODE</b> | R4                   |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.00 | 5.00 |
|------------|------|------|
| 50         | 3550 | -    |
| 10         | -    | 5600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.