


AGRIMAX RT 765

| | |
|---------------------|---|
| TIRE SIZE | 620/70 R 42 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 160 D |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94063116 | RC (IN) | 226.1 |
| SW (IN) | 24.6 | RIM REC | DW 20 B |
| OD (IN) | 76.2 | RIM ALT | DW 18 L |
| SLR (IN) | 34.5 | ECE | E11-106R-005835 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|-------|-------|-------|
| 40 | 5460 | 6350 | 7240 | 8130 | 9030 | 9920 |
| 30 | 5730 | 6670 | 7610 | 8540 | 9480 | 10420 |
| 25 | 5990 | 6970 | 7940 | 8920 | 9900 | 10870 |
| 20 | 6280 | 7310 | 8330 | 9360 | 10380 | 11410 |
| 5 LT | 7320 | 8510 | 9710 | 10900 | 12100 | 13290 |
| 5 HT | 6280 | 7310 | 8330 | 9360 | 10380 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.