

# FLOTATION 648

	<b>650/65 - 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESİ / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	162 A8/158 B
	174 A8/170 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	670	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1660	<b>ECE</b>	E11-106R-004558
<b>SLR (MM)</b>	710	<b>PR</b>	12
<b>RC (MM)</b>	4935		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.60	1.70
10 FR	8715	9050	9380
20 FR	7845	8145	8440
30 FR	6970	7240	7505
40 FR	6225	6465	6700
50 FR	5605	5820	6000
10 DW	6180	6420	6650
20 DW	5565	5775	5985
30 DW	4945	5135	5320
40 DW	4415	4585	4750
50 DW	3975	4125	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.