


AGRIMAX RT 765

TIRE SIZE	600/70 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	152 D



DIMENSIUNI US STANDARD

USA CODE	94062256	RC (IN)	188.0
SW (IN)	24.1	RIM REC	DW 20 B
OD (IN)	63.1	RIM ALT	DW 18 L; W 18 L
SLR (IN)	28.0	ECE	E11-106R-005523

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	4310	5020	5720	6430	7130	7830
30	4530	5270	6010	6750	7480	8220
25	4720	5490	6260	7030	7800	8580
20	4960	5760	6580	7390	8200	9010
5 LT	5780	6720	7660	8610	9560	10490
5 HT	4960	5760	6580	7390	8200	9010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.