

# RIB 774 (A)

<b>TIRE SIZE</b>	<b>18X8.50 - 8</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	85 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94056910	<b>RC (IN)</b>	54.7
<b>SW (IN)</b>	8.9	<b>RIM REC</b>	7.00   - 55 ;   - 70 ;   - 90
<b>OD (IN)</b>	18.1	<b>ECE</b>	E11-106R-004622
<b>SLR (IN)</b>	8.5	<b>PR</b>	6

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>44</b>
5 FR	1590
15 FR	1360
20 FR	1270
25 FR	1140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.