


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>320/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	113 A8 ; 113 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	319	<b>RIM REC</b>	W10
<b>OD (MM)</b>	982	<b>RIM ALT</b>	W9 ; W11
<b>SLR (MM)</b>	441	<b>ECE</b>	E11-106R-006944
<b>RC (MM)</b>	2916	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	635	740	840	945	1050	1150
40	635	740	840	945	1050	1150
30	680	795	905	1015	1125	1235
10 LT	850	990	1130	1270	1410	1545
10 HT	680	795	905	1015	1125	1235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.