


AGRIMAX V- FLECTO

TIRE SIZE	VF 900/65 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	193 D



DIMENSIONER US STANDARD

USA CODE	94513703	RC (IN)	271.1
SW (IN)	36.2	RIM REC	DW 30B
OD (IN)	91.1	ECE	E11-106R-0011165
SLR (IN)	39.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	11760	13600	15450	17530	19150	20760	23070
FROM 40 TO 25	12930	14960	16990	19270	21040	22820	25350
20	13180	15260	17320	19640	21460	23270	25860
12	13440	15550	17660	20030	21880	23720	26370
5	14220	16450	18680	21190	23140	25100	27890
*UPTO 5 CYC WITH FRONT LOADER	18110	20945	23790	26985	29465	31945	35495
5 HT	13180	15260	17320	19640	21460	23270	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.