

# AGRIMAX SPARGO

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>VF 320/90 R 54</b> |
| <b>UM</b>           | US STANDARD           |
| <b>CONSTRUCTION</b> |                       |
| <b>MACHINERY</b>    | TRACTOR               |
| <b>VERSION</b>      | STANDARD              |
| <b>TIRE TYPE</b>    | TL                    |
| <b>LI/SS</b>        | 168 D                 |



## DIMENSIONS US STANDARD

|                 |          |                |                            |
|-----------------|----------|----------------|----------------------------|
| <b>USA CODE</b> | 94075249 | <b>RC (IN)</b> | 234.1                      |
| <b>SW (IN)</b>  | 12.7     | <b>RIM REC</b> | W 11                       |
| <b>OD (IN)</b>  | 76.7     | <b>RIM ALT</b> | W 10; DW 10; W 10 L; DW 11 |
| <b>SLR (IN)</b> | 35.8     | <b>ECE</b>     | E11-106R-009070            |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 14   | 17   | 20   | 23   | 26   | 29   | 32   | 35   | 38   | 41    | 44    | 47    | 49    | 52    | 55    | 58    | 61    | 64    |
|----------------------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>45</b>            | 4920 | 5490 | 6180 | 6750 | 7090 | 7430 | 7670 | 7890 | 8290 | 8690  | 9030  | 9370  | 9660  | 9950  | 10230 | 10520 | 10970 | 11420 |
| <b>FROM 40 TO 25</b> | 5320 | 5940 | 6670 | 7290 | 7670 | 8030 | 8280 | 8530 | 8960 | 9400  | 9760  | 10130 | 10440 | 10750 | 11060 | 11370 | 11870 | 12350 |
| <b>20</b>            | 5430 | 6060 | 6820 | 7450 | 7820 | 8190 | 8450 | 8700 | 9140 | 9580  | 9960  | 10340 | 10650 | 10970 | 11280 | 11600 | 12110 | 12600 |
| <b>12</b>            | 5530 | 6180 | 6950 | 7590 | 7970 | 8360 | 8610 | 8870 | 9320 | 9770  | 10160 | 10540 | 10860 | 11180 | 11500 | 11820 | 12340 | 12850 |
| <b>5</b>             | 5850 | 6530 | 7350 | 8020 | 8430 | 8830 | 9110 | 9390 | 9860 | 10330 | 10740 | 11150 | 11490 | 11820 | 12160 | 12500 | 13040 | 13580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.