


AGRIMAX RT 765

TYRE SIZE	620/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR / IMPLEMENTS
VERSION	SPECIAL
TYRE TYPE	TL
LI/SS	173 D



DIMENSIONS IS STANDARD

SW (MM)	625	RIM REC	DW 20 B
OD (MM)	1935	RIM ALT	DW 18 L
SLR (MM)	876	ECE	E11-106R-005833
RC (MM)	5804	SRI	925

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	2535	2990	3445	3835	4290	4680	5135	5525	6045	6500
50	2665	3140	3620	4030	4505	4915	5395	5805	6350	6825
40	2780	3280	3775	4205	4700	5130	5625	6055	6625	7120
30	2920	3440	3965	4415	4935	5385	5910	6355	6955	7475
10 LT	3400	4010	4620	5140	5750	6275	6885	7405	8105	8710
10 HT	2920	3440	3965	4415	4935	5385	5910	6355	6955	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.