


AGRIMAX V- FLECTO

| | |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE | VF 650/65 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 169 D |



DIMENSIONER IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 650 | RIM REC | DW 23 B |
| OD (MM) | 1811 | RIM ALT | DW 21 B |
| SLR (MM) | 798 | ECE | E11-106R-005022 |
| RC (MM) | 5387 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|--------------------------------|------|------|------|------|------|------|
| 70 | 2950 | 3480 | 3955 | 4430 | 4850 | 5275 |
| FROM 65 TO 40 | 3245 | 3825 | 4350 | 4870 | 5335 | 5800 |
| 30 | 3305 | 3900 | 4435 | 4965 | 5440 | 5915 |
| 20 | 3370 | 3975 | 4520 | 5060 | 5545 | 6030 |
| 10 | 3565 | 4205 | 4785 | 5355 | 5865 | 6380 |
| *UPTO 10 CYC WITH FRONT LOADER | 4540 | 5355 | 6090 | 6815 | 7465 | 8120 |
| 10HT | 3305 | 3900 | 4435 | 4965 | 5440 | 5915 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.