

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>620/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94063482	<b>RC (IN)</b>	220.1
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	72.2	<b>RIM ALT</b>	DW 18 L; W 18 L
<b>SLR (IN)</b>	32.6	<b>ECE</b>	E11-106R-005997

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
40	5160	6080	7010	7800	8730	9520	10450	11240	12300	13230
30	5420	6390	7360	8200	9170	10010	10980	11810	12920	13890
25	5650	6670	7680	8550	9570	10440	11450	12310	13480	14480
20	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210
5 LT	6920	8160	9400	10460	11710	12760	14010	15070	16490	17720
5 HT	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.