


AT 621

| | |
|---------------------------|--|
| TIRE SIZE | 12.5/80 - 18 |
| UM | US STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | CARGADORA COMPACTA / CARGADORA RETROEXCAVADORA / CARGADORA RETROEXCAVADORA / PALA CARGADORA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 135 A8 |
| LI/SS FREE ROLLING | 148 A8 |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94026258 | RC (IN) | 114.8 |
| SW (IN) | 12.1 | RIM REC | W 9 |
| OD (IN) | 38.9 | RIM ALT | 11.0 |
| SLR (IN) | 17.1 | ECE | E11-106R-006957 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 71 |
|-----------|------|
| 5 FR | 9720 |
| 15 FR | 8270 |
| 20 FR | 7780 |
| 25 FR | 6940 |
| 5 DW | 6720 |
| 15 DW | 5720 |
| 20 DW | 5380 |
| 25 DW | 4810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.