


# AGRIMAX V- FLECTO

TIRE SIZE	VF 480/60 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	145 D



## ABMESSUNGEN US STANDARD

USA-CODE	94060740	RC (IN)	149.9
SW (IN)	18.5	RIM REC	DW 16 L
OD (IN)	50.8	RIM ALT	W 16 L
SLR (IN)	22.5	ECE	E11-106R-005496

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	3200	3710	4230	4760	5280	5810
FROM 40 TO 25	3520	4090	4660	5240	5810	6395
20	3580	4170	4750	5330	5920	6510
12	3650	4240	4840	5450	6040	6650
5	3860	4500	5130	5750	6380	7030
*UPTO 5 CYC WITH FRONT LOADER	4920	5720	6530	7330	8120	8950
5 HT	3580	4170	4750	5330	5920	6510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.