

MINE STAR



MINE STAR



MINE STAR is a bias-ply tire which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tire life-cycle.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø15"	38X16 -15	TT	-	32		11.5	-	0		39.0	0	0	35.91	STD
	35X15 -15	TT	-	32	-	11.0	11.50 11.00 BD	0		34.8	0	0	29.61	STD
	8.25 - 15	TT	-	20	-	6.5	6.0 7.0	0		33.4	0	0	23.94	STD
	35X15 -15	TT	-	20	-	11.0	11.50 11.00 BD	0		34.8	0	0	29.61	STD
	35X15 -15	TL	-	32	-	11.0	11.50 11.00 BD	0		34.8	0	0	29.61	STD

STD: STANDARD

TECHNOLOGIES			PERFORMANCES		
					
					
-	-				

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
	32X14.50/15 -15	TT	-	28		11.0	11.50 11.00 BD 10.50	0		32.5	0	0	29.61	STD
	38X16 -15	TL	-	32		11.5	-	0		39.0	0	0	35.91	STD
Ø25"	55X19.00 -25	TL	L5	50	-	14.00	-	0		55.1	24.9	168.5	86.94	STD
Ø34"	55X19.00 -34	TL	L5	50	-	16.00	-	0		56.5	0	0	80.64	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
  L5		  	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026