


AGRIMAX RT 657

TIRE SIZE	650/65 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDIMIADORA / TRACTOR / COSECHADORA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	165 D ; 168 A8



DIMENSIONES US STANDARD

CÓDIGO USA	94029501	RC (IN)	228.7
SW (IN)	25.4	RIM REC	DW 20 B
OD (IN)	75.3	RIM ALT	DW 21 B; DW 23 B
SLR (IN)	34.6	ECE	E4-106R-000625

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	5460	6360	7150	7950	8750	9420	10450	11400
30	5730	6680	7520	8360	9190	9910	10980	11930
25	5930	6920	7780	8640	9510	10250	11360	12350
20	6270	7320	8230	9150	10060	10850	12030	13060
5 LT	7310	8530	9600	10660	11730	12640	14010	15220
5 HT	6270	7320	8230	9150	10060	10850	12030	13060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.