

# AGRIMAX SIRIO

<b>TIRE SIZE</b>	<b>IF 600/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	HIGH SPEED
<b>TL/TT</b>	TL
<b>LI/SS</b>	165 D ; 162 E



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94044849	<b>RC (IN)</b>	187.4
<b>SW (IN)</b>	23.7	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	DW 20 B
<b>SLR (IN)</b>	28.1	<b>ECE</b>	E4-106R-000817

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4850	5570	6400	7240	8050	8880	9590	10330
<b>FROM 40 TO 25</b>	5340	6130	7040	7950	8860	9760	10550	11360
20	5550	6380	7310	8260	9210	10150	10970	11810
15	5660	6500	7460	8430	9390	10340	11180	12030
12	5760	6620	7600	8580	9560	10530	11390	12260
5	6770	7790	8930	10090	11240	12380	13400	14420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.