


# RM 500

<b>TIRE SIZE</b>	<b>500/80 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ERNTMASCHINE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 A8 ; 164 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	503	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1495	<b>RIM ALT</b>	W 15 L
<b>SLR (MM)</b>	635	<b>ECE</b>	E11-106R-005990
<b>RC (MM)</b>	4355	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2
<b>40 FREE ROLLING</b>	2770	3195	3550	4405	5045	5825	6605	7100
<b>40 DRIVE WHEEL</b>	1950	2250	2500	3100	3550	4100	4650	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.