

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>320/85 R 28</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 124 A8/B           |

### ABMESSUNGEN US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA-CODE</b> | 94041923 | <b>RC (IN)</b> | 148.8          |
| <b>SW (IN)</b>  | 13.0     | <b>RIM REC</b> | W 11           |
| <b>OD (IN)</b>  | 49.4     | <b>RIM ALT</b> | W 9 ; W 10     |
| <b>SLR (IN)</b> | 22.7     | <b>ECE</b>     | E4-106R-000757 |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 1940 | 2260 | 2580 | 2900 | 3220 | 3530 |
| <b>25</b>   | 1940 | 2260 | 2580 | 2900 | 3220 | 3530 |
| <b>20</b>   | 2080 | 2420 | 2770 | 3110 | 3450 | 3780 |
| <b>5 LT</b> | 2600 | 3030 | 3460 | 3880 | 4310 | 4730 |
| <b>5 HT</b> | 2080 | 2420 | 2770 | 3110 | 3450 | 3780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

