


AGRIMAX V-FLECTO

TIRE SIZE	VF 900/60 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	195 D



РАЗМЕРЫ US STANDARD

USA CODE	94511273	RC (IN)	252.4
SW (IN)	35.4	RIM REC	DW 30B
OD (IN)	84.3	ECE	E11-106R-0010587
SLR (IN)	37.2		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41
45	10240	11950	13410	15110	16820	18530	20720	22190	24370
FROM 40 TO 25	11250	13130	14740	16610	18480	20360	22770	24380	26780
20	11470	13390	15020	16940	18850	20770	23220	24860	27310
12	11710	13660	15320	17270	19220	21170	23680	25350	27850
5	12380	14440	16210	18280	20340	22400	25050	26820	29460
UPTO 20 CYCLIC	12780	14900	16720	18850	20990	23110	25850	27670	30400
UPTO 10 CYCLIC	15240	17790	19960	22510	25040	27580	30850	33020	36290
UPTO 5 CYCLIC	16710	19500	21880	24670	27460	30230	33820	36210	39780
5 HT	11470	13390	15020	16940	18850	20770	23220	24860	27310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.