DATA SHEET

Latest update
2-06-2026

AGRIMAX RT 955

TYRE SIZE	**340/85 R 48**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	IMPLEMENTS
VERSION	STANDARD
TL/TT	TL
LI/SS	151 D ; 154 A8

DIMENSIONS IS STANDARD

SW (MM)	353	**RIM REC**	W 12
OD (MM)	1797	**RIM ALT**	W 11
SLR (MM)	855	**ECE**	E11-106R-005765
RC (MM)	5572	**SRI**	875

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
65	1485	1660	1865	2040	2245	2385	2625	2830	3005	3175	3450
50	1560	1740	1960	2140	2360	2505	2755	2975	3155	3335	3625
40	1615	1800	2025	2215	2440	2590	2850	3075	3265	3450	370
30	1710	1910	2145	2345	2585	2740	3020	3260	3455	3655	3970
10	2230	2485	2975	3055	3365	3575	3935	4245	4505	4765	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..