


AGRIMAX FORCE



TIRE SIZE	IF 420/85 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	155 D

DIMENSIONI IS STANDARD

SW (MM)	419	RIM REC	DW 14 L
OD (MM)	1670	RIM ALT	DW 15 L
SLR (MM)	780	ECE	E11-106R-004897
RC (MM)	5017	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	1655	1900	2180	2465	2745	3030	3310	3525
FROM 65 TO 40	1820	2090	2400	2710	3020	3330	3640	3875
30	1890	2170	2495	2815	3140	3460	3785	4030
20	1965	2255	2590	2925	3260	3595	3930	4185
10	2310	2650	3045	3440	3835	4225	4620	4920
*UPTO 10 CYC WITH FRONT LOADER	2545	2925	3360	3790	4225	4660	5095	5425
10 HT	1890	2170	2495	2815	3140	3460	3785	4030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.