

# AGRIMAX RT 855

|                     |                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>420/85 R 38</b>                                                                          |
| <b>UM</b>           | IS STANDARD                                                                                 |
| <b>CONSTRUCTION</b> |  RADIAL    |
| <b>MACHINERY</b>    | PULVÉRISATEUR / MACHINE À<br>VENDANGER / TRACTEUR /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE |
| <b>VERSION</b>      | STANDARD                                                                                    |
| <b>TIRE TYPE</b>    | TL                                                                                          |
| <b>LI/SS</b>        | 144 A8/B                                                                                    |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 438  | <b>RIM REC</b> | W 15 L         |
| <b>OD (MM)</b>  | 1679 | <b>RIM ALT</b> | W 13 ; W 14 L  |
| <b>SLR (MM)</b> | 763  | <b>ECE</b>     | E4-106R-000661 |
| <b>RC (MM)</b>  | 5014 | <b>SRI</b>     | 800            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 1540 | 1795 | 2045 | 2300 | 2550 | 2800 |
| <b>40</b>    | 1540 | 1795 | 2045 | 2300 | 2550 | 2800 |
| <b>30</b>    | 1650 | 1920 | 2190 | 2460 | 2730 | 3000 |
| <b>10 LT</b> | 2070 | 2405 | 2745 | 3080 | 3420 | 3755 |
| <b>10 HT</b> | 1650 | 1920 | 2190 | 2460 | 2730 | 3000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.