

AS 504

TIRE SIZE	7.5L - 15
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	97 A8
LI/SS FREE ROLLING	109 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	210	RIM REC	6 LB
OD (MM)	765	RIM ALT	5 K; 5½ J; 5½ K
SLR (MM)	354	ECE	E11-106R-004238
RC (MM)	2280	PR	6

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	1440
25 FR	1225
30 FR	1155
40 FR	1030
10 DW	1020
25 DW	870
30 DW	820
40 DW	730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.