


# RIDEMAX IT 697 (M+S)



<b>TIRE SIZE</b>	<b>460/70 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 A8 ; 152 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94067039	<b>RC (IN)</b>	148.5
<b>SW (IN)</b>	18.3	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	49.4	<b>RIM ALT</b>	DW14 L; DW 16L
<b>SLR (IN)</b>	22.5	<b>ECE</b>	E11-106R-006840

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	3910	4780	5250	6180	6970	7830
30	4230	5160	5670	6680	7530	8450
25	4550	5560	6100	7190	8100	9090
20	4700	5730	6290	7430	8370	9390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.